


Options

| Other connection |                                    |               |
|------------------|------------------------------------|---------------|
| I3               | Actuator programming input / reset |               |
| I5               | EDM input                          | Not connected |

| Connection    |                                                       |
|---------------|-------------------------------------------------------|
| Safety switch | A1 Supply input +24 Vdc                               |
|               | A2 Supply input 0 Vdc                                 |
|               | IS1 Safety input                                      |
|               | OS1 Safety output                                     |
|               | IS2 Safety input                                      |
|               | OS2 Safety output                                     |
|               | IE1 Solenoid activation input for double channel mode |
|               | IE2 Solenoid activation input for double channel mode |
|               | O3 Signalling output, actuator inserted               |
|               | O4 Signalling output, actuator inserted and locked    |
|               | I4 Solenoid activation input for single channel mode  |

| Contacts |     | Diagram |                |
|----------|-----|---------|----------------|
| Device 1 | 1NO |         | 17<br>18 19    |
|          |     |         |                |
| Device 2 | 1NO |         | 15<br>16 19    |
|          |     |         |                |
| Device 3 | 2NC |         | 11<br>10 13 14 |
|          |     |         |                |



|           |                                |  |
|-----------|--------------------------------|--|
| Connector | M23 with 19 pole at the bottom |  |
|-----------|--------------------------------|--|

